

JCS04 U.S. PTO

PATENT APPLICATION TRANSMITTAL LETTER

(Small Entity)

Docket No.

MADE-0001

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Transmitted herewith for filing under 35 U.S.C. 111 and 37 C.F.R. 1.53 is the patent application of:

For: UNIVERSAL FIXTURE SYSTEM AND BASE THEREFOR

Enclosed are:

- ☒ Certificate of Mailing with Express Mail Mailing Label No. EJ228693452US
- ☒ 9 sheets of drawings.
- ☐ A certified copy of a application.
- ☒ Declaration ☒ Signed. ☐ Unsigned.
- ☒ Power of Attorney
- ☒ Information Disclosure Statement
- ☐ Preliminary Amendment
- ☒ Verified Statement(s) to Establish Small Entity Status Under 37 C.F.R. 1.9 and 1.27.
- ☐ Other:

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	44	- 20 =	24	x \$9.00	\$216.00
Indep. Claims	5	- 3 =	2	x \$39.00	\$78.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$380.00
TOTAL FILING FEE					\$674.00

- ☒ A check in the amount of \$674.00 to cover the filing fee is enclosed.
- ☐ The Commissioner is hereby authorized to charge and credit Deposit Account No. as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of as filing fee.
- ☐ Credit any overpayment.
- ☐ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: August 3, 1999



Signature

RONALD A. D'ALESSANDRO
REG. NO. 42,456

CC:

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) AND 1.27 (b)) - INDEPENDENT INVENTOR**

Docket No.
MADE-0001

Serial No.

Filing Date

Patent No.

Issue Date

Applicant/ **THOMAS MADELONE**
Patentee:

Invention: **UNIVERSAL FIXTURE SYSTEM AND BASE THEREFOR**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled above and described in:

- ☒ the specification to be filed herewith.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern or organization exists.
☐ Each such person, concern or organization is listed below.

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 CFR 1.27)

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR THOMAS MADELONE

SIGNATURE OF INVENTOR Thomas Madelone

DATE: 8/3/99

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

NAME OF INVENTOR _____

SIGNATURE OF INVENTOR _____

DATE: _____

UNIVERSAL FIXTURE SYSTEM AND BASE THEREFOR

Background of the Invention

1. Technical Field

The present invention generally relates to a universal
5 fixture system and base therefor, and more particularly to a
fixture system and base that includes separately adjustable
segments and is adapted to hold multiple tools and/or workpieces.

2. Background Art

10 In the use and manipulation of tools, it is often necessary
for a workpiece or tool to be secured in a particular position
while leaving the hands of a user free. For example, when a user
is repairing a workpiece, the workpiece may need to be secured in
a vice or similar retaining mechanism. In addition, tools such
15 as drills, screwdrivers, clamps, or flashlights may need to be
held or placed in specific positions relative to the workpiece.
With such needs, the hands of a user are not free to repair the
workpiece, instead, being consumed when the user has to hold the
workpiece or tools. Moreover, a user may need to adjust portions
20 or segments of the fixture system without effecting the other
segments.

Heretofore, many have attempted to solve such problems by
employing inferior variations. Examples include the following,

all of which are herein incorporated by reference:

U.S. Patent No. 1,670,253 to A. Gilbert et al.;

U.S. Patent No. 3,883,128 to Breese;

U.S. Patent No. 4,125,251 to Jamieson, Jr.;

5 U.S. Patent No. 4,253,649 to Hewson;

U.S. Patent No. 4,258,908 to Goff et al. and

U.S. Patent No. 4,500,077 to Coxon.

10 U.S. Patent No. 4,253,649 to Hewson teaches an adjustable
positioning tool that includes a series of components. With the
invention of Hewson, however, when a user attempts to re-position
one shaft segment, the preceding shaft segment will also be re-
positioned. This will cause the tool or workpiece, disposed
adjacent the preceding shaft segment, to also be re-positioned.
In addition, Hewson fails to teach a base, or similar structure,
15 onto which the positioning tool can be mounted so that multiple
tools and a workpiece can be simultaneously held without
requiring the user's hands.

20 U.S. Patent No. 1,670,253 to A. Gilbert et al. discloses a
welding structure for holding workpieces in place as they are
welded together. Similar to Hewson, Gilbert et al. utilizes a
system of rods and clamps for securing the workpieces in place.
However, the device of Gilbert et al. requires adjustment of
multiple fasteners to provide for the vertical positioning of a
workpiece. Such a feature is both time consuming and tedious for

a user. In addition, the device Gilbert *et al.* is designed to hold workpieces in planar alignment with each other for welding. This is such that a user is denied the ability to position the workpieces at various positions about a rotational axis.

5 U.S. Patent No. 4,500,077 to Coxon discloses a device for clamping that comprises a components. However, similar to the above-discussed references, the adjustment of one rod segment of Coxon requires adjustment of multiple fasteners and potentially, other rod segments.

10 Therefore, there exists the need for a fixture system, and base therefor, that is adjustable by a user so as to hold multiple tools and/or workpieces in varying positions about a rotational axis. In addition, there exists the need for such a fixture system and base to be adjustable by a user such that one
15 segment or portion of the fixture system can be adjusted without effecting other segments or portions.

Summary of the Invention

20 The present invention overcomes the deficiencies of the related art by including a universal fixture system and base that is capable of holding multiple tools and/or workpieces in various positions about a rotational axis. In addition, the present invention overcomes the deficiencies of the related art by providing a fixture system in which single segments or portions

are adjustable independent of the other segments.

According to one aspect of the present invention, a fixture system is provided, which includes: (1) a base having at least one set of support brackets and an aperture; (2) a first support member adapted for connection to one set of support brackets, wherein the support member includes a shaft having a coupling joined thereto; (3) a first connector, extending through one set of support brackets and the shaft, for securing the support member to the one set of support brackets; and (4) a rod having a first end and a second end, wherein the first end is coupled to the coupling.

According to a second aspect of the present invention, a fixture system is provided, which includes: (1) a first rod having a first end and a second end; (2) a housing having a channel and a housing coupling, wherein the second end of the first rod is coupled to the housing coupling; (3) a first support member having a shaft and a coupling, wherein the shaft is coupled to the channel of the housing; and (4) a second rod having a first end and a second end, wherein the first end of the second rod is coupled to the coupling of the support member.

According to a third aspect of the present invention, a fixture system is provided, which includes: (1) a clamp; (2) a rod having a first end and a second end, wherein the first end is coupled to the clamp; (3) a housing having a channel and a

housing coupling, wherein the second end of the rod is coupled to the housing coupling; (4) a support member having a shaft and a coupling, wherein the shaft of the support member is coupled to with the channel of the housing; and (5) a second rod having a first end and a second end, wherein the first end of the second rod is coupled to the coupling of the support member.

According to a fourth aspect of the present invention, a base is provided, which includes: (1) an elongate body having a first end and a second end; (2) a first set of support brackets positioned adjacent the first end and a second set of support brackets positioned adjacent the second end, wherein each set of support brackets includes a thru-hole and a fastener; and (3) a threaded aperture, positioned between the first and second ends of the base.

According to a fifth aspect of the present invention, a fixture system is provided, which includes: (1) a housing having a channel and a housing coupling; and (2) a support member having a shaft and a coupling, wherein the support member is adapted to couple to the housing.

It is therefore an advantage of the present invention to provide fixture system and base therefor for holding multiple tools and/or workpieces in various positions about a rotational axis. It is also an advantage of the present invention to provide a fixture system and base therefor in which unitary

segments of the fixture system are adjustable without effecting other segments.

The preferred embodiment of the invention is designed to solve the problems herein described and other problems not discussed, which are discoverable by a skilled artisan.

Brief Description of the Drawings

These and other features and advantages of this invention will be more readily understood from the following detailed description of the various aspects of the invention taken in conjunction with the accompanying drawings in which:

Fig. 1 is a perspective view of a fixture system and base in accordance with the present invention;

Fig. 2 is an exploded view of the components of the fixture system, in accordance with the present invention;

Fig. 3A is a top view of a base, in accordance with the present invention;

Fig. 3B is a front view of the fixture system and base, in accordance with the present invention;

Fig. 4A is front view of a support member, in accordance with the present invention;

Fig. 4B is a right side view of the support member of Fig. 4A, in accordance with the present invention;

Fig. 5A is a front view of a housing, in accordance with the

present invention;

Fig. 5B is a right side view of the housing of Fig. 5A, in accordance with the present invention;

Fig. 6A is a front view of a base plate assembly, in accordance with the present invention;

Fig. 6B is a top view of the base plate assembly of Fig. 6A, in accordance with the present invention;

Fig. 7 is a front view of a stand, in accordance with the present invention;

Fig. 8 is a front view of a magnetic base, in accordance with the present invention;

Fig. 9 is a side view of a fixture system with the magnetic base of Fig. 8, in accordance with the present invention;

Fig. 10 is a front view of a dial indicator holder, in accordance with the present invention; and

Fig. 11. is a front view of a fixture system having the dial indicator holder of Fig. 10, in accordance with the present invention.

It is noted that the drawings of the invention are not to scale. The drawings are merely schematic representations, not intended to portray specific parameters of the invention. The drawings are intended to depict only typical embodiments of the invention, and therefore should not be considered as limiting the scope of the invention. In the drawings, like numbering

represents like elements between the drawings.

Detailed Description of the Drawings

Referring now to the drawings, Fig. 1 shows the assembled
fixture system 10 and Fig. 2 shows the various components
thereof. Referring to Fig. 2, base 14 generally includes
opposing sets of support brackets 12 each having a thru-hole 15,
and an aperture 11. Aperture 11 is preferably threaded and
extends completely through the base 14. In addition, as shown in
Fig. 3A, a nut, fastener, or similar fastening device 30 is
disposed on each set of support brackets 12 opposite the thru-
hole 15. Preferably, the nut 30 is welded onto each set of
support brackets 12, however, it should be understood that other
equivalent mechanisms of affixing the nut 30 to the support
brackets 12 exist.

Next, a support member 32 is shown in detail in Figs. 4 and
4A. Generally, support member 32 is comprised of a shaft 33
having a thru-hole 37 and a coupling 35 joined thereto.
Preferably, the coupling 35 is threaded and is welded to the
shaft 33. However, it should be understood that many mechanisms
of achieving attachment of the shaft 33 to the coupling 35 could
be implemented.

Shown in detail in Figs. 5A and 5B is a housing 24. Housing
24 includes a channel 28, a housing coupling 26 joined to the

channel 28, a nut or fastener 30 affixed to the channel 28, and a thru-hole 31 disposed through a side of the channel 28 opposite the nut or fastener 30. Similar to the coupling 35 of the support member 32, the housing coupling 26 is internally threaded. Moreover, both the nut 30 and the housing coupling 26 are preferably welded to the channel 28. However, similar to the above components, it should be appreciated that many equivalent mechanisms of affixing the nut 30 and housing coupling 26 exist.

Shown in Fig. 2 is a rod 22, wing nut 20, and a handle or connector 16. Rod 22 is preferably externally threaded so as to couple to or engage the couplings 26 and 35 of the housing 24 and support member 32, respectively. In addition, wing nuts 20 are dimensioned to thread onto the rod 22 and to more firmly secure the rod 22 into the couplings 26 and 35. Connector or handle 16 includes a pair of flared handles 19 having flat portions 21 disposed on the ends thereof, and a threaded portion 17 for engaging the thru-hole 31 of the housing 24, the shaft 33 of the support member 32 and then securing into the nut or fastener 30, as will be described in further detail below. The configuration of the handle 16 is advantageous because, *inter alia*, the flared handles 19 allow a user to generate increased torque in tightening or loosening the handle 16. In addition, the flat portions 21 provide a user with additional leverage and surface area with which they can grip the handle 16. Thus, resulting in

more efficient use of the handle 16.

To use the fixture system 10 a user will assemble the various components as shown in Figs. 2 and 3B. First, the base 14 is provided. Into each set of support brackets 12, a user will insert a support member 32. Specifically, the support member is inserted with the shaft 33 of the support member being lined-up with the thru-hole 15 and nut 30 of the set of support brackets 12 and the coupling 35 extending vertically away from the set of support brackets 12. This will allow a user to insert a handle or connector 16 into the thru-hole 15 of each set of support brackets 12 so that the threaded portion 17 is placed through the thru-hole 37 of the shaft 33 and then threadedly secured into the nut 30. Thus, locking the support member 32 into place within the set of support brackets 12. In addition, although the coupling 35 of the support member 32 is shown in Fig. 3B as being substantially upright or vertical, it should be appreciated that the described system of inter-fitting the components allows for a user to position the coupling 35 at various positions along a radius. For example, the coupling 35 could be secured into position at any angle within horizontal borders of the base 14. Preferably, each support bracket in the sets of support brackets 12 is approximately 1 ½" in width x 1 ½" in height with the thru-hole being approximately ½" in diameter. Moreover the shaft 33 of the support member 32 is preferably 1 ½"

in length with a $\frac{1}{2}$ " diameter thru-hole. These dimensions will allow for the support member 32 to fit snugly within the set of support brackets 12. With respect to the handle 16, the threaded portion 11 thereof is preferably approximately $\frac{1}{2}$ " - 13 and the flared handles 19 provide approximately 2" of grip length. These dimensions will allow a user to thread the handle 16 into the nut 30 affixed to the set of support brackets 12, which is preferably a $\frac{1}{2}$ -13 nut.

Once the shaft 33 of the support member 32 is secured in the desired position, a rod 22 is then threaded into the coupling 35 of the support member 32. Since the coupling is preferably a $\frac{1}{2}$ " - 13 coupling, the rod is also preferably $\frac{1}{2}$ " in diameter. However, the precise length of the rod will vary depending on the needs of the user. Once the rod 22 is threadedly coupled to the coupling 35 of the support member 32, a wing nut 20 or other similar fastening device with a dimension of approximately $\frac{1}{2}$ " - 13 can be utilized to ensure that the rod 22 is locked within the coupling 35. Although threaded engagements can ensure a secure fit between components, vibrational motion caused by tools attached to the fixture system may adversely effect the integrity of the interconnection. Accordingly, the use of wing nuts 20, or the like is preferred. It should be also appreciated many known equivalents to wing nuts 20 exist and can be employed with similar results.

The other end of the rod 22 is then threaded into the housing coupling 26 of the housing 24 to complete the first segment of the fixture system. Preferably, the housing coupling 26 has the same dimensions as the coupling 35 of the support member 32. Specifically, the housing coupling 26 is approximately $\frac{1}{2}$ " - 13 and is welded or otherwise affixed to the channel 28. Once again, a wing nut 22 or other similar fastening device can be used to ensure a secure interconnection between the rod 22 and the housing coupling 26. After the rod 22 is secured within the housing coupling 26, a second support member 32' is secured within the channel 28 of the housing 24 in the same manner as described above with respect to the set of support brackets 12. Namely, the shaft 33' of the second support member 32' is positioned within the channel 28 of the housing 24, with the thru-hole 37 of the shaft 33' being aligned with the thru-hole 31 of the housing 24. Once aligned, a connector or handle 16 is inserted into the thru-hole 31 of the housing 24, through the thru-hole 37 of the shaft 33' and into the fastener or nut 30 affixed to the channel 24 of the housing 24. The thru-holes of both the housing 24 and the shaft 33' are preferably $\frac{1}{2}$ " in diameter while the fastener 30 is approximately a $\frac{1}{2}$ " - 13 nut and is preferably welded to the channel 28. However, it should be appreciated that many other means of affixing the fastener 30 to the channel 28 exists.

The handle 16 can then be rotated to tighten or loosen the junction between the second support member 32' and the housing 24. In addition, similar to the support member 32 positioned within the set of support brackets 12, the second support member 32' in the housing 24 can be positioned at various positions along a rotation axis, thus, giving a user increased flexibility with respect to the positioning of the fixture system 10. Once the coupling 35' of the second support member 32' is in the desired position, the user can then add another segment to the fixture system 10. Specifically, as shown in Fig. 3B, a second rod 22', of approximately 3/8" - 16, can be threaded into the 3/8" - 16 coupling 35' of the second support member 32' and then secured with a 3/8" - 16 wing nut 20.

This second rod 22' is preferably threaded and, as shown in. 3B, is threaded into a housing coupling 26' of a second housing 24'. Similar to the previous segment, the housing coupling 26' of the second housing 24' should have the same dimensions as the second threaded rod 22', namely 3/8" - 16 so as to ensure a tight fit. In addition, another 3/8" - 16 wing nut 20' can be utilized between the second rod 22' and the housing coupling 26' of the second housing 24' to further ensure a tight fit. Once the second rod 22' is threadedly secured within the housing coupling 26' of the second housing 24', a third support member 32'' can be interconnected within the second housing 24', with the use of

another handle or connector 16. Once again, the user will secure the support member by positioning the shaft 33'' within the housing 24' so that the ½" thru holes 37 and 31 are in alignment. Then, the handle 16 will be passed through the shaft 33'' and into the fastener or nut 30 affixed to the channel 28' of the second housing 24'. Preferably, the coupling of the third support member 32'' is approximately 3/8" - 16 while the fastener or nut affixed to the channel 28' is approximately ½" - 13.

Finally, a third rod segment 22'', is threadedly coupled to the coupling 35'' of the third support member 32'' and if desirable, is further secured with a wing nut 20''. Preferably, the third rod segment 22'' and the wing nut 20'' are approximately 3/8" - 16 while the third rod segment 22'' is about 6" in length and is bent at an angle. Once assembled, a user is then free to threadedly engage tools, or the like with the free end of the third rod 22''. Examples of such tools, include, *inter alia*, screwdrivers, drills, clamps, or flashlights. It should be appreciated, however, that the third rod 22'' need not be limited in size or bent at any angle.

It should also be appreciated that the number of segments in the fixture system and all dimensions given in this description are for illustrative and best mode purposes only and are not intended to be limiting. For example, a user could assemble a fixture system 10 having fewer or greater number of segments

and/or where all components are of larger, smaller, or equivalent dimensions. In addition, all components are preferable comprised of a metal, such as carbon or stainless steel. However, it should be appreciated that many equivalents exist, such as hardened plastics. Moreover, Fig. 3B, and the description given thereof, depicts only one side/arm of the fixture system 10. However, it should be understood that complimentary components are used in assembling the other side(s)/arm(s) and segments of the system 10.

Referring now to Figs. 6A and 6B, a metal base plate assembly 34 is shown. Specifically, base plate assembly 34 includes base plate 36, base coupling 38, and nipple 40. Preferably, base plate 36 is approximately a 1/4" carbon steel plate that is welded to the 1" base coupling 38. The nipple 40 is preferably a 1" threaded nipple that is threadedly coupled within the base coupling 38. Disposed on the top surface of the base plate 36 are mounting slots 42. Once again, it should be understood that the dimensions, materials, and means for affixing cited for these components are for best mode and illustrative purposes and it should be understood that many equivalent variations exist. For example, the base plate assembly 34 need not be metal and can be constructed with varying dimensions. In addition, the base coupling 38 need not be welded to the base plate 36.

Once base plate assembly 34 is constructed, it is threadedly coupled to the aperture 11 of base 14, as shown in Figs. 1 and 2. This allows for a tool, such as a vice 100, to be mounted onto the base plate 36 through the mounting slots 42. The vice 100 will enable a user to secure a workpiece in a desired position while leaving his/her hands free to manipulate the fixture system 10, or the tools fixed thereto.

Fig. 7 shows a stand 44 that is also adapted to coupled to the base 14. Specifically, the stand 44 includes a 24" x 24" x 3/16" steel mounting plate 46 that is welded to a 6" steel channel 48. Welded to the channel 48 is a 1 1/4" steel pipe 50 of optional length. Fitted into the steel pipe 50 is a 1" steel pipe 54, of optional length, having a 1" threaded nipple 40, that is approximately 2" in length, welded thereto. The overall lengths of the pipe segments 50 and 54 are optional depending on the needs of the user. In addition, the interconnection of the second pipe segment 54 within the first pipe segment 50 allows for the overall height of the stand to be adjusted. This adjustment is controlled with a connector or handle 52, which is inserted into an aperture 53 in the first pipe segment 50 and abutted against the second pipe segment. Thus, by rotating the handle 52, a user can lock the second pipe segment 54 into position within the first pipe segment 50 at any desired height.

Once the desired height of the stand 44 is achieved, the

base 14 can then be mounted thereon. This is accomplished by
threading the nipple 55 into the bottom side of the aperture 11
in the base 14. In cases where the base plate assembly 34 is
also desired to be used, the presence of the stand will not
interfere. In contrast, the base 14 is so designed such that
both components can be threaded into the aperture 11, without
interfering with one another. It should be appreciated that
these specific dimensions and materials for the stand have been
disclosed for best mode and illustrative purposes only.
Accordingly, users may vary the materials used and the dimensions
thereof equivalently.

Figs. 8-11 show alternative bases that can be used in
conjunction with the fixture system 10. Referring, first to Figs.
8 and 9, a magnetic base 70 is shown. The magnetic base 70
generally includes footing 78 having support brackets 72 affixed
thereto. Support brackets 72 preferable include a $\frac{1}{2}$ " thru-hole
and a $\frac{1}{2}$ " - 13 nut welded thereto while the footing 70 includes
slots 80 and orifice 82. To affix a magnet 84 to the base, a
user will insert the magnet 84 through the orifice 82 and bolt
the magnet to the footing 78 through slots 80. Preferably, the
magnetic base 70 is comprised of a metal, the slots 80 are $\frac{3}{8}$ ",
and the orifice is at a 60° angle. However, it should be
understood that these characteristics have many known equivalents
and are given for illustrative and best mode purposes only.

Fig. 9, shows the magnetic base in use. As can be seen, the base can have application where space is limited, and/or a metallic surface is present onto which the magnet base can be secured. To assemble the fixture system on the magnetic base 70, a user will follow the same steps set forth in assembling the fixture system 10 onto the base 14. Specifically, a support member 32 is inserted into the support brackets 72 and secured by positioning a handle 16 through thru-holes 74 and 37 and into fastener or nut 76.

Fig. 11 shows the fixture system 10 with a clamp 90 as a base. As shown, the clamp 90 can be any known clamp that has an aperture for threading. To assemble the fixture system 10, a user will affix the clamp 90 onto a desired surface and then thread a rod 22 into the aperture in the clamp 90. From there, a user can add wing nuts 20, 20', and 20'', housings 24 and 24', couplings 32 and 32', and additional rod segments as desired.

Referring now to Figs. 10 and 11, a dial indicator holder 56 is shown. Specifically, the dial indicator holder 56 is preferably attached to the outermost rod of the fixture system 10, as shown in Fig. 11, and allows a user to attach a dial indicator to the fixture system. The dial indicator holder 56 is generally comprised of a 3/8" tool coupling 58 welded to a shaft 60 that has a 3/8" diameter thru-hole 61 and a 1/4" - 20 tapped hole 62. Welded to the shaft 60 is an elongate support segment

64 that is welded to a tip 66 that has a 1/4" diameter tapped hole.

To affix a dial indicator 92 to the dial indicator holder 56, a user will thread the rod 22'' into the tool coupling 58 of the dial indicator holder 56 and, if desired, secured the connection with a wing nut 20'', if desired. Once the holder 56 is firmly attached to the rod 22'', the dial indicator 92 is secured onto the shaft 60 by placing a thumb screw 94, or other similar fastener, through the tapped hole 62 and into an aperture disposed along the back surface of the dial indicator 92. Once again, the precise materials and dimensions set forth are for illustrative and best mode purposes only, and it should be understood that many equivalents exist.

The foregoing description of the preferred embodiments of this invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed, and obviously, many modifications and variations are possible. Such modifications and variations that may be apparent to a person skilled in the art are intended to be included within the scope of this invention as defined by the accompanying claims.

Claims

1 1. A fixture system comprising:

2 a base having at least one set of support brackets;

3 a first support member, adapted for connection to one set of
4 support brackets, wherein the support member includes a shaft
5 having a coupling joined thereto;

6 a first connector, extending through one set of support
7 brackets and the shaft, for securing the support member to the
8 one set of support brackets; and

9 a rod having a first end and a second end, wherein the first
10 end is coupled to the coupling.

11 2. The system of claim 1, wherein the at least one set of support
12 brackets is welded to the base.

13 3. The system of claim 1, wherein the at least one set of support
14 brackets each include:

15 a thru-hole; and

16 a fastener, positioned proximate the thru-hole.

17 4. The system of claim 3, wherein the connector includes a pair
18 of flared handles and a threaded portion for engaging the thru-
19 hole of the one set of support brackets and threadedly securing

4 to the fastener.

1 5. The system of claim 1, wherein the base includes a threaded
2 aperture.

1 6. The system of claim 1, wherein the coupling is threaded and is
2 welded to the shaft.

1 7. The system of claim 1, wherein the rod is threaded.

1 8. The system of claim 1, further comprising a housing that
2 engages the rod, wherein the housing comprises:
3 a channel; and
4 a housing coupling affixed to the channel.

1 9. The system of claim 8, wherein the channel is metal.

1 10. The system of claim 8, wherein the housing coupling is
2 threaded and is welded to the channel.

1 11. The system of claim 8, wherein the second end of the rod is
2 coupled to the housing coupling.

1 12. The system of claim 11, further comprising means for securing
2 the second end of the rod to the housing coupling.

1 13. The system of claim 8, further comprising a second support
2 member coupled to the housing, wherein the second support member
3 also includes a shaft having a coupling joined thereto.

1 14. The system of claim 13, further comprising a second connector
2 for securing the second support member to the housing.

1 15. The system of claim 14, further comprising a second rod
2 having a first end and a second end, wherein the first end of the
3 second rod is coupled to the coupling of the second support
4 member.

1 16. The system of claim 15, further comprising means for locking
2 the first end of the second rod to the coupling of the second
3 support member.

1 17. The system of claim 15, further comprising a tool coupled to
2 the second end of the second rod.

1 18. The system of claim 1, further comprising a stand that is
2 adapted to couple to the base.

1 19. The system of claim 18, wherein the stand comprises:
2 a mounting plate;
3 a channel secured to the mounting plate;
4 a first pipe segment affixed to the channel;
5 a second pipe segment for slidably engaging the first pipe
6 segment, wherein the second pipe segment includes an end that is
7 threaded; and
8 means for locking the second pipe segment into place within
9 the first pipe segment.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226

1 22. A fixture system comprising:
2 a first rod having a first end and a second end;
3 a housing having a channel and a housing coupling, wherein
4 the second end of the first rod is coupled to the housing
5 coupling;
6 a first support member having a shaft and a coupling,
7 wherein the shaft is coupled to the channel of the housing; and
8 a second rod having a first end and a second end, wherein
9 the first end of the second rod is coupled to the coupling of the
10 support member.

1 23. The system of claim 22, further comprising means for locking
2 the rods to the couplings.

1 24. The system of claim 22, further comprising means for locking
2 the support member to the housing.

1 25. The system of claim 22, wherein the second end of the second
2 rod is coupled to a tool and wherein the tool comprises:
3 a tool coupling;
4 a shaft, affixed to the tool coupling, wherein the shaft has
5 a first thru-hole;
6 a support segment affixed to the shaft; and
7 a tip, affixed to the support segment, wherein the tip has a

8 second thru-hole.

1 26. The system of claim 22, further comprising:

2 a base; and

3 a second support member having a shaft and a coupling,

4 wherein the first end of the first rod is coupled to the coupling

5 of the second support member, and wherein the shaft of the second

6 support member is coupled to the base.

1 27. The system of claim 26, wherein the base includes a magnet.

1 28. The system of claim 26, wherein the base is a clamp.

1 29. The system of claim 26, wherein the base includes at least
2 one set of support brackets.

1 30. The system of claim 29, wherein the base further includes a
2 threaded aperture.

1 31. The system of claim 30, further comprising a base plate
2 assembly, coupled within the aperture, wherein the assembly
3 includes a base plate having a base coupling affixed thereto.

1 32. The system of claim 29, further comprising a stand coupled to
2 a lower portion of the aperture of the base.

1 33. The system of claim 32, wherein the stand comprises:

2 a mounting plate;

3 a channel secured to the mounting plate;

4 a first pipe segment affixed to the channel;

5 a second pipe segment for slidably engaging the first pipe

6 segment, wherein the second pipe segment includes an end that is

7 threaded; and

8 means for locking the second pipe segment into place within
9 the first pipe segment.

1 34. A fixture system, comprising
2 a clamp;
3 a first rod having a first end and a second end, wherein the
4 first end is coupled to the clamp;
5 a housing having a channel and a housing coupling, wherein
6 the second end of the rod is coupled to the housing coupling;
7 a support member having a shaft and a coupling, wherein the
8 shaft is coupled to the channel of the housing; and
9 a second rod having a first end and a second end, wherein
10 the first end of the second rod is coupled to the coupling of the
11 support member.

1 35. The system of claim 34, wherein rods threadedly engage the
2 couplings.

1 36. The system of claim 34, further comprising means for securing
2 the support member to the housing.

1 37. The system of claim 34, further comprising means for securing
2 the rods to the couplings.

1 38. A base, comprising:
2 an elongate body having a first end and a second end;
3 a first set of support brackets positioned adjacent the
4 first end and a second set of support brackets positioned
5 adjacent the second end, wherein each set of support brackets
6 includes a thru-hole, and a fastener; and
7 a threaded aperture between the first and second ends of the
8 base.

1 39. The base plate of claim 38, wherein the fastener is affixed
2 to the channel, proximate the thru-hole.

1 40. The base of claim 38, further comprising a base plate
2 assembly, wherein the base plate assembly includes:
3 a base plate;
4 a base coupling affixed to the base plate; and
5 a threaded segment for engaging the threaded aperture in the
6 base.

1 41. The base plate assembly of claim 40, wherein the base plate
2 comprises a plurality of mounting slots for mounting a tool
3 thereon.

1 42. A fixture system comprising:
2 a housing having a channel and a housing coupling; and
3 a support member having a shaft and a coupling, wherein the
4 support member is adapted to couple to the housing.

1 43. The fixture system of claim 42, wherein the shaft of the
2 support member is adapted to couple to the channel of the
3 housing.

1 44. The fixture system of claim 42, further comprising a first
2 and a second rod, wherein an end of the first rod is adapted to
3 couple to the housing coupling and an end of the second rod is
4 adapted to couple to the coupling of the support member.

Abstract of the Disclosure

UNIVERSAL FIXTURE SYSTEM AND BASE THEREFOR

A universal fixture system and base therefor is provided that is capable of holding multiple tools and/or workpieces in various positions about a rotational axis. In addition, the fixture system and base allows for single segments or portions to be adjusted independent of the other segments. The fixture system and base include: (1) a base having at least one set of support brackets; (2) a support member, having a shaft and a coupling joined thereto, adapted for connection to one set of support brackets; (3) a connector extending through one set of support brackets and the shaft; and (4) a rod having a first end that is coupled to the coupling.